

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A method, comprising:

initializing a virus scanner during a pre-boot phase of a computer system from
firmware that is embedded within the computer system;

scrubbing data read from an input/output (I/O) device of the computer system by
the virus scanner using a virus signature database before the data is loaded, wherein the
virus signature database is stored in a place not exposed to the operating system and is
updated during the pre-boot phase; and

enacting a platform policy if a virus is detected in the data.
2. (Original) The method of claim 1, further comprising scrubbing contents
of a memory device of the computer system during the pre-boot phase by the virus
scanner.
3. (Original) The method of claim 1, further comprising updating the virus
signature database with updated virus signatures.
4. (Original) The method of claim 3 wherein the virus signature database is
updated during the pre-boot phase.

5. (Original) The method of claim 1 wherein the virus signature database is not exposed to an operating system executing on the computer system.

6. (Original) The method of claim 5 wherein the virus signature database is stored in a firmware-reserved area.

7. (Previously Presented) The method of claim 1 wherein the virus scanner is executing in a virtual machine monitor (VMM) executing on the computer system, the VMM supporting at least one virtual machine (VM) executing on the computer system, wherein the VM executes an operating system that is different from the VMM and the operating systems executed by other VMs.

8. (Original) The method of claim 7 wherein scrubbing data read from the I/O device includes:

receiving a request from a requester to read data from the I/O device, the requester in a VM of the at least one VM;

loading at least a portion of the requested data into a buffer;

scrubbing the at least a portion of the requested data with the virus scanner;

returning an error signal to the requester if the virus scanner detects a virus in the at least a portion of the requested data; and forwarding the requested data to the requester if the virus scanner does not detect a virus in the at least a portion of the requested data.

9. (Original) The method of claim 1 wherein the virus scanner is operable during the pre-boot phase, an operating system (OS) runtime phase, and an after-life phase of the computer system independent of an operating system of the computer system.

10. (Original) The method of claim 1 wherein the virus scanner scrubs the data without having knowledge of a file system of the data.

11. (Original) The method of claim 1, further comprising enacting the platform policy if the virus scanner detects non-normal behavior within the computer system.

12. (Currently Amended) An article of manufacture comprising:
a machine-accessible medium including a plurality of instructions which when executed perform operations comprising:
initializing a virus scanner during a pre-boot phase of a computer system;
scrubbing contents of a memory device of the computer system during the pre-boot phase by the virus scanner using a virus signature database from firmware that is embedded within the computer system;
scrubbing data read from an input/output (I/O) device of the computer system by the virus scanner using the virus signature database before the data is loaded, wherein the virus signature database is stored in place not exposed to the operating system and is updated during the pre-boot phase; and

generating an error signal if a virus is detected by the virus scanner.

13. (Original) The article of manufacture of claim 12, further comprising receiving updated virus signatures at the computer system to update the virus signature database.

14. (Original) The article of manufacture of claim 12 wherein the virus signature database is stored in a place not exposed to an operating system of the computer system.

15. (Original) The article of manufacture of claim 12 wherein the virus scanner to be operable during the pre-boot phase, an operating system (OS) runtime phase, and an after-life phase of the computer system independent of an operating system of the computer system.

16. (Original) The article of manufacture of claim 12 wherein the virus scanner to scrub the data without having knowledge of a file system of the data.

17. (Original) The article of manufacture of claim 12 wherein scrubbing data read from the I/O device includes:

launching a virtual machine monitor (VMM), the virus scanner to operate from the VMM; and

launching a virtual machine (VM) to be supported by the VMM.

18. (Original) The article of manufacture of claim 17 wherein execution of the plurality of instructions further perform operations comprising:

receiving a request from a requester in the VM to read data from the I/O device;
loading at least a portion of the requested data into a buffer;
scrubbing the at least a portion of the requested data with the virus scanner;
returning an error signal to the requester if the virus scanner detects a virus in the at least a portion of the requested data; and
forwarding the requested data to the requester if the virus scanner does not detect a virus in the at least a portion of the requested data.

19. (Previously Presented) The article of manufacture of claim 12 wherein the plurality of instructions is to operate in compliance with an Extensible Firmware Interface (EFI) specification.

20. (Currently Amended) A computer system, comprising:
a processor;
a memory device operatively coupled to the processor;
a storage device operatively coupled to the processor; and
at least one flash memory device operatively coupled to the processor, the at least one flash memory device including firmware instructions which when executed by the processor perform operations comprising:

initializing a virus scanner during a pre-boot phase of a computer system
from the firmware;

scrubbing contents of the memory device during the pre-boot phase by the
virus scanner using a virus signature database, wherein the virus signature
database is stored in a place not exposed to the operating system and is updated
during the pre-boot phase;

scrubbing data read from the storage device by the virus scanner using the
virus signature database before the data is loaded in the memory device; and
generating an error signal if a virus is detected by the virus scanner.

21. (Original) The computer system of claim 20, further comprising a
network interface operatively coupled to the processor, the virus scanner to scrub data
read from the network interface using the virus signature database before the data is
loaded in the memory device.

22. (Original) The computer system of claim 20 wherein the virus signature
database is stored in a firmware reserved area of the storage device, the firmware
reserved area not exposed to an operating system of the computer system.

23. (Original) The system of claim 20 wherein execution of the firmware
instructions further perform operations comprising updating the virus signature database
with updated virus signatures downloaded from an external virus signature repository
communicatively coupled to the computer system.

24. (Original) The computer system of claim 20 wherein the virus scanner is operable during the pre-boot phase, an operating system (OS) runtime phase, and an after-life phase of the computer system independent of an operating system of the computer system.

25. (Original) The computer system of claim 20 wherein the virus scanner to scrub the data without having knowledge of a file system of the storage device.

26. (Previously Presented) The computer system of claim 20 wherein the firmware instructions to operate in compliance with an Extensible Firmware Interface (EFI) specification.

27-30. (Canceled)